




FireNET Plus® - DIGITAL ANALOG ADDRESSABLE FIRE ALARM CONTROL PANEL SPECIFICATIONS

Primary AC	120VAC @ 2.1 Amps 50/60hz or 220VAC @ 1.1Amps 50/60hz
Output DC	24VDC @ 5.25 Amps
Power Supply	4 Amp integrated
Charger Current	1.25 Amps max.
Dimensions	14.5" W x 19" H x 3.5" D
Weight	20 lbs. (without batteries)
Color	Red (optional gray)
Material	ABS/steel enclosure
Display	8 line x 40 character LCD (320 character total)
Network	Dual RS485 ports (64 panels max.)
Zones	500 network wide software zones per system
SLC loops	1 or 2 (class A, "style 6 or 7" or class B, "style 4")
Devices per loop	127 sensors & modules, plus 127 digital analog sounder bases, 254 total
Addresses per panel	800 addresses + sub-addresses max. per panel
NAC Outputs	(2) class B, 2.3 Amps (special application) 1.6 Amps Regulated (continuous)
Relay Outputs	(3) Form C 1 Amp @ 30VDC
Aux. Power	2 outputs, 360mA @ 24VDC each
PC Port / Printer	RS232
DACT Formats	Contact ID and SIA

SLC COMPATIBLE DEVICES & SYSTEM ACCESSORIES

MODEL	DESCRIPTION
CONTROL PANEL EXPANDERS	
FNP-1127-SLC	SLC One Loop Expansion Card
FN-4127-NIC	Network Interface Card
FN-4127-IO	16 Channel Input/Output Board
ANNUNCIATOR	
FN-LCD-S	Serial LCD Annunciator
FNP-LED	Graphix Display
SLC LOOP DEVICES	
ALG-V, ALK-V, ALN-V	Digital Analog Addressable Photoelectric Sensor
AIE-EA	Digital Analog Addressable Ionization Sensor
ATG-EA, ATJ-EA	Digital Analog Addressable Heat Sensor
ACA-V, ACC-V, ACD-V	Multi-criteria Sensor
NSA-4 & NSA-6	Four Inch Sensor Base and Six Inch Sensor Base
SCI-B4 & SCI-B6	Four Inch Short Circuit Isolator Digital Analog Sensor Base & Six Inch Circuit Isolator Digital Analog Sensor Base
ASB	 Sounder Base
ASBL	 Low Frequency Sounder Base
DH-98A, DH-98AR	 Addressable Duct Detector Unit
DH-99A, DH-99AR	(DH-98AR and DH-99AR have relays built-in)
MS-RA, MS-RA/R, MS-KA/R	Remote Test Station for DH-98AR & DH-99AR
DCP-FRCME-M	Contact Monitoring Module (mini w/terminal blocks)
DCP-FRCME-P	Contact Monitoring Module (mini w/pigtail leads)
DCP-FRCME-4	Contact Monitoring Module (with faceplate/indicating LED)
DCP-FRCMA, DCP-FRCMA-I	Class A Contact Monitoring Module (FRCMA-I has built-in SCI)
DCP-DIMM	Dual Input Monitor Module (with faceplate/indicating LED)
DCP-CZM	Conventional Zone Module
DCP-R2M	Dual Relay Module
DCP-R2ML/H Series	Dual Relay Module (R2ML-I & R2MH-I has built-in SCI)
DCP-SOM	Supervised Output Module
DCP-SOM-A, DCP-SOM-AI	Class A Supervised Output Module (SOM-AI has built-in SCI)
DCP-SOM-R	Supervised Output Module for Releasing Pre-action System
DCP-SCI	Short Circuit Isolator Module
DCP-AMS Series	Addressable Manual Pull Station
ACCESSORIES	
TCH-B100	Hand Held Programmer (portable device addresser)
FN-ACC	Battery/Accessory Enclosure (houses up to 33AH size batteries)
FNP-ETR	Enclosure Trim Ring for panel flush mount